

EXANE® ZH-1105A METRIC

TRANSIT WIRE, 600V-1000V

125 °C • Transit Wire • 600V - 1000V

Spec. DAA1105A



FEATURES

- Superior Flame Retardance
- Exceptional wet electrical properties
- Enhanced Mechanical toughness
- Wide temperature range -45 °C to 125 °C
- Thermoset Insulation
- Excellent oil/solvent resistance
- Sunlight resistant
- Low Smoke
- Zero Halogen
- Voltage Rating 600/1000V

PERFORMANCE STANDARDS

- Satisfies performance requirements of BS EN 50265-2-1: 1999 (IEC 60332-2-2: 2004)
- Satisfies performance requirements of BS EN 50265-2-2:1999 (IEC 60332-2-1: 2004)
- Satisfies the requirements for BS 6853:1999 vehicle category 1a for vehicles interior and exterior per:
 - BS 6853: 1997 Annex D 8.7
 - BS 6853: 1999, Clause 6.2, Table 13&14
 - BS 6853: 1999 Annex B.1
- Satisfies performance requirements of IEC 60754-1
- Satisfies performance requirements of IEC 60754-2

CONSTRUCTION

Conductor: Annealed, Tinned copper per IEC 60228, Class 5/BS6360

Insulation: Crosslinked low smoke halogen free polymer (colors-as required)

* RSCC rated 125 °C, 130 °C overload, 250 °C short circuit

SCOPE

Exane®-ZH, Low Smoke Zero Halogen transit wire is a tough, highly flame retardant construction ideally suited for use in rugged locomotive and transportation industry applications. It has excellent electrical characteristics combined with superior mechanical, heat, moisture, oil, chemical and abrasion properties. This wire should be considered for applications where flame resistance and low levels of off gassing and toxic fumes are required.

CHICAGO

933 E. Remington Rd
Schaumburg, IL 60173
847.944.1500

BOSTON

100 Jytek Drive
Leominster, MA 01453
978.534.5300

ATLANTA

5940 Cabot Parkway
Alpharetta, GA 30005
678.297.1080

PHOENIX

1524 W 14th Street
Tempe, AZ 85281
623.478.8700

EXANE® ZH-1105A METRIC TRANSIT WIRE, 600V-1000V, 125°C



Conductor mm ²	Conductor Construction #/mm Dia	Conductor Diameter mm	Nominal Wall Thickness mm	Nominal Ins. Diameter mm	DCR** Ω/kg	Weight KG/100 M	Blend Radius mm
0.75	24/0.20	1.17	0.76	2.74	26.7	1.63	10.96
1	32/0.20	1.35	0.76	2.92	20.0	1.74	11.68
1.5	30/0.25	1.52	0.76	3.10	13.7	2.29	12.40
2.5	50/0.25	2.06	0.76	3.63	8.21	3.46	14.52
4	56/0.30	2.62	0.76	4.19	5.09	5.02	16.76
6	84/0.30	3.20	0.76	4.78	3.39	7.13	19.12
10	80/0.40	4.19	1.14	6.54	1.95	12.95	26.16
16	126/0.40	5.31	1.14	7.66	1.24	19.33	30.64
25	196/0.40	7.11	1.14	9.46	0.80	29.16	37.84
35	276/0.40	8.51	1.14	10.86	0.57	40.00	43.44
50	396/0.40	10.31	1.40	13.18	0.39	57.66	52.72
70	360/0.50	12.40	1.40	15.27	0.28	77.15	61.08
95	475/0.50	14.50	1.40	17.37	0.21	100.34	69.48
150	756/0.50	18.01	1.65	21.40	0.13	158.18	85.60
240	1221/0.50	21.64	1.65	25.03	0.08	239.70	100.12
300	1525/0.50	26.01	2.03	30.20	0.07	314.90	120.80
400	2013/0.50	27.94	2.03	32.11	0.05	406.98	128.44

*According to ICEA 5-66-524.

**According to IEC 60228.

STRIPING IS AVAILABLE.

Exane® is a registered trademark RSCC Wire & Cable LLC

CHICAGO
933 E. Remington Rd
Schaumburg, IL 60173
847.944.1500

BOSTON
100 Jytek Drive
Leominster, MA 01453
978.534.5300

ATLANTA
5940 Cabot Parkway
Alpharetta, GA 30005
678.297.1080

PHOENIX
1524 W 14th Street
Tempe, AZ 85281
623.478.8700

For sales inquiries: sales@electrowire.com